


GY Series Y-type globe valve for power station as per ANSIB16.34



Main size of outside and weight


Model: J65Y-1500Lb, J565Y-1500Lb, J965Y-1500Lb

NPS	L	d	Hand-operated			Geared driving			Geared	Electric driving device			Electric
(in)			н	Do	Weight (kg)	н	Do	Weight (kg)	driving	н	Do	Weight (kg)	driving device
21/2	330	56	670	360	45	-	-	-	-	-	-	-	-
3	368	64	750	460	70	-	-	-	2	990	305	200	SMC-0
4	457	84	830	510	110	-		-	-	990	305	310	SMC-1
5	533	100	910	560	129	1100	460	505	BA-1	1115	305	514	SMC-1
6	610	126	1100	610	180	1730	610	520	BA-2	1763	457	534	SMC-2
8	762	158	-		-	2010	610	820	BA-2	2026	457	950	SMC-2

Main size of outside and weight

Model: J565Y-2000Lb, J965Y-2000Lb

NPS (in)	L		Hand-operated			Geared driving			Geared	Electric driving device			Electric
			н	Do	Weight (kg)	.H.:	Do	Weight (kg)	driving	н	Do	Weight (kg)	driving device
4	457	80		870	460	214		BA-1	990	305	327		SMC-1
5	533	96		995	460	303		BA-1	1115	305	408		SMC-1
6	610	118		1025	610	470		BA-2	1423	457	470		SMC-2
8	762	148		1505	610	980		BA-2	1615	457	1050		SMC-2
10	914	180		1825	760	1280		BA-3	2240	610	1582		SMC-4
12	1041	222		2300	610	2714		B-4-PA-2	2490	610	2	340	SMC-4



Main size of outside and weight

Model: J65Y-2500Lb, J565Y-2500Lb, J965Y-2500Lb

NPS (in)	L	d	Hand-operated			G	Geared driving			Electric driving device			Electric
			н	Do	Weight (kg)	н	Do	Weight (kg)	Geared driving	н	Do	Weight (kg)	driving device
2	310	38	550	300	42	-	-	-	-	810	305	130	SMC-00
21/2	340	46	670	360	72	-	-	_	-	895	305	160	SMC-00
3	390	54	750	460	81	750	310	121	BA-0	995	305	217	SMC-0
4	480	70	830	720	130	870	460	212	BA-1	990	305	337	SMC-1
5	580	86	-	-	-	995	460	312	BA-1	1115	305	432	SMC-1
6	630	104	-	-	(+)	1205	610	410	BA-2	1280	457	652	SMC-2
8	770	130	1	2	_	1565	610	1060	BA-2	1615	457	1122	SMC-2
10	930	162	-77	-5	100	1870	760	1380	BA-3	1930	610	1652	SMC-3
12	1060	210	_	2	-	2335	760	2824	B-4-PA-2	2240	610	2862	SMC-4
14	1160	234	-	-		2515	760	3624	B-4-PA-2	2420	610	3662	SMC-4

Main size of outside and weight

Model: J565Y-3500Lb, J965Y-3500Lb

NPS (in)	L		Hand-operated			Geared driving			Geared	Electric driving device			Electric
			н	Do	Weight (kg)	H	Do	Weight (kg)	driving	н	Do	Weight (kg)	driving device
3	470	48		817	310	172		BA-0	1005	305	272		SMC-0
4	550	60		930	310	293		BA-0	1133	305	387		SMC-0
5	660	74		1075	460	462		BA-1	1280	305	582		SMC-1
6	790	88		1220	460	727		BA-1	1320	305	847		SMC-1